

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

## SAFETY CLEAN AEROSOL

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** : SAFETY CLEAN AEROSOL  
**Registration number REACH** : Not applicable (mixture)  
**Product type REACH** : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Novatio\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
✉ +32 14 22 02 66  
info@novatio.be  
\*NOVATIO is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
✉ +32 14 85 97 38  
info@tec7.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements



Contains: hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics.

**Signal word** Danger

##### H-statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

##### P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.

# SAFETY CLEAN AEROSOL

P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

## Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 01-2119471843-32		C>30%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 3; H412	(1)(10)	UVCB
butane 01-2119474691-32	106-97-8 203-448-7	15%<C<30%	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant
propane 01-2119486944-21	74-98-6 200-827-9	5%<c<15%	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, seek medical advice.

#### After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

#### After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

#### After eye contact:

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists.

#### After ingestion:

Rinse mouth with water. Consult a doctor/medical service if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Central nervous system depression. Narcosis.

##### After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

##### After eye contact:

No effects known.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher.

#### 5.1.2 Unsuitable extinguishing media:

Reason for revision: 5; 8.1; 15

Publication date: 2010-07-09

Date of revision: 2018-07-10

Revision number: 0307

Product number: 49027

2 / 12

# SAFETY CLEAN AEROSOL

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam.

Major fire: Water (water can be used to control jet flame), Foam.

## 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

## 5.3. Advice for firefighters

### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

### 5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves. Protective clothing.

Suitable protective clothing

See heading 8.2

### 6.2. Environmental precautions

Dam up the liquid spill.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material, e.g.: dry sand/earth. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See heading 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Remove contaminated clothing immediately.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Meet the legal requirements.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

##### Belgium

Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4)	Time-weighted average exposure limit 8 h	1000 ppm
---	--	----------

##### France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
----------	--	---------

# SAFETY CLEAN AEROSOL

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>
----------	--	------------------------

## Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup>

## UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

Butane, all isomers	Short time value (TLV - Adopted Value)	1000 ppm
---------------------	--	----------

## b) National biological limit values

If limit values are applicable and available these will be listed below.

### 8.1.2 Sampling methods

If applicable and available it will be listed below.

### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

### 8.1.4 DNEL/PNEC values

#### DNEL/DMEL - Workers

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	871 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	77 mg/kg bw/day	

#### DNEL/DMEL - General population

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	185 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	46 mg/kg bw/day	
	Long-term systemic effects oral	46 mg/kg bw/day	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN374).

Materials	Measured breakthrough time	Thickness	Protection index
nitrile rubber	> 480 minutes	0.35 mm	Class 6

#### c) Eye protection:

Protective goggles.

#### d) Skin protection:

Head/neck protection. Protective clothing.

### 8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	No data available on colour

Reason for revision: 5; 8.1; 15

Publication date: 2010-07-09

Date of revision: 2018-07-10

Revision number: 0307

Product number: 49027

4 / 12

# SAFETY CLEAN AEROSOL

Particle size	Not applicable (mixture)
Explosion limits	0.6 - 9.5 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	700 mPa.s ; 20 °C ; Liquid
Kinematic viscosity	921 mm <sup>2</sup> /s ; 20 °C ; Liquid
Melting point	No data available
Boiling point	-45 °C - 166 °C ; Liquid
Evaporation rate	0.35 ; Butyl acetate ; Liquid
Relative vapour density	> 1
Vapour pressure	8530 hPa ; 20 °C
Solubility	Water ; insoluble
Relative density	0.76 ; 20 °C ; Liquid
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Flash point	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

## 9.2. Other information

Absolute density	760 kg/m <sup>3</sup> ; 20 °C ; Liquid
------------------	--

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

No data available.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Take precautions against electrostatic charges.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### 11.1.1 Test results

#### Acute toxicity

##### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male/female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3160 mg/kg bw	24 h	Rabbit (male/female)	Read-across	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5.6 mg/l air	4 h	Rat (male/female)	Read-across	

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

##### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Reason for revision: 5; 8.1; 15

Publication date: 2010-07-09

Date of revision: 2018-07-10

Revision number: 0307

Product number: 49027

5 / 12

# SAFETY CLEAN AEROSOL

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		1; 24; 48; 72; 168 hours	Rabbit	Read-across	Single treatment
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

## Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

## Respiratory or skin sensitisation

### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (female)	Read-across	

## Conclusion

Not classified as sensitizing for skin

## Specific target organ toxicity

### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 422	> 1000 mg/kg bw/day		No effect		Rat (male/female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 10400 mg/m <sup>3</sup> air		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Read-across

## Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Read-across

## Mutagenicity (in vivo)

### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 478	5 days (6h/day)	Rat (male/female)		Read-across

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 5; 8.1; 15

Publication date: 2010-07-09

Date of revision: 2018-07-10

Revision number: 0307

Product number: 49027

6 / 12

# SAFETY CLEAN AEROSOL

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 453	≥ 2200 mg/m <sup>3</sup> air	105 weeks (6h/day, 5 days/week)	Rat (female)	No carcinogenic effect		Read-across

## Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	≥ 5220 mg/m <sup>3</sup> air	10 days (6h/day)	Rat	No effect		Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	> 5220 mg/m <sup>3</sup> air	10 days (6h/day)	Rat	No effect		Read-across
Effects on fertility	NOAEL	Equivalent to OECD 413	> 1000 mg/kg bw/day	14 weeks (6h/day, 5 days/week)	Rat (male/female)	No effect		Read-across

## Conclusion

Not classified for reprotoxic or developmental toxicity

## Toxicity other effects

### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
				Skin dryness or cracking			Literature study

## Conclusion

Repeated exposure may cause skin dryness or cracking.

## Chronic effects from short and long-term exposure

### SAFETY CLEAN AEROSOL

No effects known.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### SAFETY CLEAN AEROSOL

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	10 mg/l - 30 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	22 mg/l - 46 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	> 1000 mg/l	72 h	Pseudokirchneria subcapitata	Static system	Fresh water	Experimental value; GLP
	NOEL	OECD 201	< 1 mg/l	72 h	Pseudokirchneria subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEL		0.182 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOELR		0.317 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Nominal concentration

## Conclusion

Harmful to aquatic life with long lasting effects.

Reason for revision: 5; 8.1; 15

Publication date: 2010-07-09

Date of revision: 2018-07-10

Revision number: 0307

Product number: 49027

7 / 12

# SAFETY CLEAN AEROSOL

## 12.2. Persistence and degradability

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	89 %	28 day(s)	Experimental value

### Conclusion

Contains readily biodegradable component(s)

## 12.3. Bioaccumulative potential

SAFETY CLEAN AEROSOL

### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

### Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

## 12.4. Mobility in soil

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	89.8 %	0 %	6.2 %	1.8 %	2.2 %	Calculated value

### Conclusion

No (test)data on mobility of the components available

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Other adverse effects

SAFETY CLEAN AEROSOL

### Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29\* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Use appropriate containment to avoid environmental contamination.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

UN number	1950
-----------	------

Reason for revision: 5; 8.1; 15

Publication date: 2010-07-09

Date of revision: 2018-07-10

Revision number: 0307

Product number: 49027

8 / 12



# SAFETY CLEAN AEROSOL

## 14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

## 14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

## 14.4. Packing group

Packing group	
Labels	2.1

## 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

## 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Rail (RID)

### 14.1. UN number

UN number	1950
-----------	------

### 14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

### 14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	5F

### 14.4. Packing group

Packing group	
Labels	2.1

### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Inland waterways (ADN)

### 14.1. UN number

UN number	1950
-----------	------

### 14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

### 14.3. Transport hazard class(es)

Class	2
Classification code	5F

### 14.4. Packing group

Packing group	
Labels	2.1

### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

### 14.1. UN number

UN number	1950
-----------	------

### 14.2. UN proper shipping name

Proper shipping name	Aerosols
----------------------	----------

### 14.3. Transport hazard class(es)

Class	2.1
-------	-----

# SAFETY CLEAN AEROSOL

## 14.4. Packing group

Packing group	
Labels	2.1

## 14.5. Environmental hazards

Marine pollutant	-
Environmentally hazardous substance mark	no

## 14.6. Special precautions for user

Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Annex II of MARPOL 73/78	Not applicable
--------------------------	----------------

## Air (ICAO-TI/IATA-DGR)

### 14.1. UN number

UN number	1950
-----------	------

### 14.2. UN proper shipping name

Proper shipping name	Aerosols, flammable
----------------------	---------------------

### 14.3. Transport hazard class(es)

Class	2.1
-------	-----

## 14.4. Packing group

Packing group	
Labels	2.1

## 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

## 14.6. Special precautions for user

Special provisions	A145
Special provisions	A167
Special provisions	A802
Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
99.67 %	
680.128 g/l	

Ingredients according to Regulation (EC) No 648/2004 and amendments

≥30% aliphatic hydrocarbons

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

Reason for revision: 5; 8.1; 15

Publication date: 2010-07-09

Date of revision: 2018-07-10

Revision number: 0307

Product number: 49027

10 / 12

# SAFETY CLEAN AEROSOL

		<p>a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</p> <p>b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</p> <p>c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.</p> <p>6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.</p> <p>7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</p>
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> <li>— metallic glitter intended mainly for decoration,</li> <li>— artificial snow and frost,</li> <li>— "whoopie" cushions,</li> <li>— silly string aerosols,</li> <li>— imitation excrement,</li> <li>— horns for parties,</li> <li>— decorative flakes and foams,</li> <li>— artificial cobwebs,</li> <li>— stink bombs.</li> </ul> <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:</p> <p>"For professional users only".</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>

## National legislation Belgium

### SAFETY CLEAN AEROSOL

No data available

## National legislation The Netherlands

### SAFETY CLEAN AEROSOL

Waterbezwaarlijkheid	Z (2)
----------------------	-------

## National legislation France

### SAFETY CLEAN AEROSOL

No data available

## National legislation Germany

### SAFETY CLEAN AEROSOL

WGK	2; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4) and Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) of 18 April 2017
-----	---

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

TA-Luft	5.2.5
---------	-------

## National legislation United Kingdom

### SAFETY CLEAN AEROSOL

No data available

## Other relevant data

### SAFETY CLEAN AEROSOL

No data available

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

Reason for revision: 5; 8.1; 15

Publication date: 2010-07-09

Date of revision: 2018-07-10

Revision number: 0307

Product number: 49027

11 / 12

# SAFETY CLEAN AEROSOL

## SECTION 16: Other information

### Full text of any H-statements referred to under heading 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

(*)	INTERNAL CLASSIFICATION BY BIG
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.